


Aerosmith High Pressure Structural Steel and Concrete Pins



HN120



When the Pressure is High...

Try Aerosmith Pins with your High Pressure Tools

- ↓ Powerful enough to drive .300" head pins into concrete
- ↓ Easily fasten subfloor, underlayment and sleepers to concrete
- ↓ 2x4 to Red Iron Steel and Concrete
- ↓ 16 ga Heavy Track to I-Beam and Concrete
- ↓ Shortens job time and increases profits
- ↓ Ultra Light weighing 6.4 lbs.
- ↓ Free of Powder Load
- ↓ Low Recoil
- ↓ Adjustable magazine plate to allow 1"-2-1/2" pin accommodation
- ↓ No Licensing Required

Call 1-800-528-8183 or visit us online at www.AerosmithFastening.com.

An **aerosmith**[®] Product...

Defining the Standard for Steel & Concrete Fastening

Aerosmith Fastening Systems
5621 Dividend Road, Indianapolis, IN 46241
Ph: 317.243.5959 Fax: 317.390.6980
Email: info@AerosmithFastening.com
www.AerosmithFastening.com



*Wood to Concrete
Drywall to Concrete
Wood to Steel*

The FASTEST way to penetrate concrete.



Aerosmith pins ensure consistent and durable fastening.



Your Local Authorized Aerosmith Distributor

Use Aerosmith Pins in Your High Pressure Tools

Aerosmith has pins for your High Pressure tools. Aerosmith .145HP pins are designed to attach Cement Fiber Siding to Block, Hardwood floor underlayment, 2x4 to Red Iron steel and Concrete and 16ga Heavy Steel Track to I-Beam/Concrete

.145 Series, Knurled and Smooth Shank Plastic Sheet Coil Collated

Shank Diameter = .145" Head Diameter = 1/4" Zinc Galvanized



Design Loads
LGSRG-2-96
LARR
RR22668
RR25264
ICC / ICBO
ER-5667
ER-5001
ESR-1799

Item	Length	Knurl	Carton	Substrate	Base Material
5253HP	1" (25mm)	Smooth	1.5 M	Steel Track	Concrete
5254HP	1" (25mm)	Helical	1.5 M	Plywood	Steel
5323HP	1-1/4" (32mm)	Smooth	1.5 M	Plywood	Concrete
5323HPG	1-1/4" (32mm)	Smooth	1.5 M	Premium Galvanization for Cement Fiber Siding to Block	Concrete
5383HP	1-1/2" (38mm)	Smooth	1.5 M	Plywood	Concrete
5383HPST	1-1/2" (38mm)	Smooth Step	1.5 M	Plywood	Concrete
5384HP	1-1/2" (38mm)	Helical	1.5 M	Plywood	Steel
5454HP	1-3/4" (44mm)	Helical	1.5 M	3/4" Cement Fiber Siding & Plywood to 3/16" Steel	Steel
5503HP	2" (51mm)	Smooth	1.5 M	2X4 to Red Iron Steel, Cement Fiber Siding to Foam to Concrete	Steel Concrete
5503HP	2" (51mm)	Smooth Step	1.5 M	2X4 to Red Iron Steel, Cement Fiber Siding to Foam to Concrete	Steel Concrete
5573HP	2-1/4" (57mm)	Smooth	1 M	Sleeper / Dim. Lumber	Concrete
5573HPG	2-1/4" (57mm)	Smooth	1 M	ACQ 2x4 Red Iron Steel & Concrete	Steel Concrete
5633HPG	2-1/2" (63mm)	Smooth	1 M	ACQ 2x4 Red Iron Steel & Concrete	Concrete

Tool Features and Accessories



Yellow Outlets
Regular Pressure



Orange Outlets
High Pressure



400 PSI Compressor
High pressure compressor
designed to operate High
Pressure tools.
(AKH1050)



Air Hose and Fittings

High pressure hose and fittings are
designed exclusively for High Pressure
tools. 100 ft./30 mm High Pressure
Hose (KHL100FTx30)



Wide range of fastener length
with adjustable magazine plate.
1" to 2-1/2" pin accommodation



HN120 Swivel
Hose Fitting

Aerosmith Fastening Systems
5621 Dividend Road, Indianapolis, IN 46241
Ph: 317.243.5959 Fax: 317.390.6980
Email: info@AerosmithFastening.com
www.AerosmithFastening.com

Aerosmith Fastening Systems (Aerosmith) does not practice structural engineering, or architectural / building design, and is not responsible for the recommendation or use of its products in situations where a professional or certified opinion is required. It is the responsibility of the end user to comply with all local building codes, project design specifications, and good building practices. For the use of building professionals, Aerosmith does provide third party evaluation reports and engineered test data performed to recognized protocols.